

APPLE cs

40 - 90 HP

Rotary mower with large side shift

The APPLE cs is a strong rotary mower for mowing grass in orchards and vineyards.

Adjustable support wheels make it possible to adjust the mower to the wheel width of the tractor. Adaptation to the ground contours is further helped by the hitch.

The cut material is discharged to the right. A subsequent modification of material discharge to the left is possible on request.



Standard version and specifications

- > Mows grass and weed up to 1 cm (0.4 inch) Ø
- > Working speed 6-9 km/h
- > Robust chassis
- > Reversible cat. 1 & 2 ISO 3-point linkage
- > Hydraulic side shift up to 58 cm (23 inch)
- > 540 rpm gearbox without freewheel with through shaft
- > Input shaft 1 3/8" Z=6
- > Lateral discharge
- > Front support wheels
- > Rear support roller with roller scarper
- > Rotor with horizontally rotating blades

Optional configuration and accessories


- > PTO drive shaft with freewheel
- > Gearbox 1000 rpm
- > Front attachment
- Herbite spraying system XID single

SPECIFICATIONS		Tractor power 40-90 HP
Working width	145 cm [57 inch]	170 cm [67 inch]
Overall width	150 cm [59 inch]	175 cm [69 inch]
Depth	168 cm [66 inch]	168 cm [66 inch]
Height	95 cm [37 inch]	95 cm [37 inch]
Weight (base value)	411 kg [906 lb]	435 kg [959 lb]
Blades	4	4



ROTOR


2 rotors / 4 blades



www.seppi.com ROTARY MOWER

Hydraulic side shift

The attachment of the APPLE cs is on the left-hand side. The parallel linkage side shift moves the mower to the right for the work under the rows of trees.





REQUIRED HYDRAULIC FITTINGS

Side shift 1 double acting

